



product_datasheet_title

LED Worklight Charge Mobile 40W 4000K

WORKLIGHT BATTERY TRIPOD | Tripod with detachable chargeable lights



technical_data

ELECTRICAL DATA

Nominal wattage	40 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	230.000 mA
Inrush current	0.4 A
Max. number of luminaires per miniature circuit breaker C10	34
Power factor λ	≥ 0.8
Total harmonic distortion	$< 40\%$
Protection class	I
Operating mode	Mains voltage

PHOTOMETRICAL DATA

Luminous flux	3600 lm
Total luminous flux of contained light sources	
Luminous efficacy	90 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥ 80
Standard deviation of color matching	< 6 sdc _m
Flickering metric (Pst LM)	$\leq 1\%$
Stroboscope effect metric (SVM)	≤ 0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	110 °

DIMENSIONS & WEIGHT

Length	1694.00 mm
Width	755.00 mm
Height	658.00 mm
Product weight	4200.00 g

LED
WORKLIGHT3X50WCHRGMOB
840TRIPOD

MATERIALS & COLORS

Product color	Orange
Housing color	Orange
Body material	Aluminum Plastic
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

APPLICATION & MOUNTING

Ambient temperature range	-10...+40 °C
Temperature range at storage	-10...+50 °C
Type of protection	IP54
Protection class IK (shock resistance)	IK05
Dimmable	no
Mounting type	Standing
Mounting location	Floor
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

LIFESPAN

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Type of Battery	Lithium ion
Battery size [GMS]	18650
Number of included batteries	2
Nominal voltage of battery	3.7 V
Battery charging time	4.5 h



EMERGENCY LIGHTING

Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	250 lm
Battery life in emergency operation mode	2 h

CERTIFICATES & STANDARDS

Standards	CE
Luminaire with limited surface temperature, "D sign"	No

download_data

Documents and certificates	document_name
 User instruction	LED WORKLIGHT 40WCHRGMOB
 Declarations Of Conformity CE	LED WORKLIGHT 40WCHRGMOB 840TRIPOD LEDV

logistical_data

product_code	packaging_unit	dimensions	weight	volume
4058075576575	Folding box 1	639 mm x 326 mm x 127 mm	4967.00 g	26.46 dm ³
4058075576582	Shipping box 2	656 mm x 343 mm x 277 mm	10716.00 g	62.33 dm ³

logistical_data_text

disclaimer_title

disclaimer_text