

product_datasheet_title

LED Star R39 25 36° 1.5W 827 E14

LED STAR R39 | LED reflector lamps R39 with retrofit screw base



technical_data

ELECTRICAL DATA

Nominal wattage	1.5 W
Construction wattage	1.50 W
Nominal voltage	220...240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	25 W
Nominal current	12 mA
Type of current	AC
Inrush current	9.6 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	330
Max. lamp number on MCB B16 A	516
Total harmonic distortion	150 %
Power factor λ	> 0.40

PHOTOMETRICAL DATA

Luminous intensity	248 cd
Luminous flux	110 lm
Nominal useful luminous flux 90°	110 lm
Luminous efficacy	73 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcn
Rated peak intensity	248 cd
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



Everlight 67-23ST KKE 2700K

LIGHT TECHNICAL DATA

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

DIMENSIONS & WEIGHT

Overall length	70.00 mm
Diameter	39.00 mm
Maximum diameter	39 mm
Product weight	36.00 g

TEMPERATURES & OPERATING CONDITIONS

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	75 °C

LIFESPAN

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

ADDITIONAL PRODUCT DATA

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
----------------	--

CAPABILITIES

Dimmable	no
----------	----

CERTIFICATES & STANDARDS

Energy efficiency class	F 1)
Energy consumption	2.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

COUNTRY-SPECIFIC CATEGORIZATIONS

Order reference	LEDSR392536 1,5
-----------------	-----------------

LOGISTICAL DATA





Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	no
Color-tuneable light source	no
Envelope	No
High luminance light source	no
Anti-glare shield	no
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	Yes
Length	70.00 mm
Height	39.00 mm

Width	39.00 mm
Chromaticity coordinate x	0.452
Chromaticity coordinate y	0.4104
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.9
Displacement factor	0.5
LED light source replaces a fluorescent light source	no
EPREL ID	1403191,522928,1841963
Model number	AC32659,AC24571,AC57952

download_data

Documents and certificates		document_name
	Declarations Of Conformity CE	R39 R50 R63 R80 LED lamp
	Declarations Of Conformity CE	LED R39 R50 PAR16
	Declarations Of Conformity UKCA	LED R39 R50 PA16
Photometric and lighting design files		document_name
	Spectral power distribution	Everlight 67-23ST KKE 2700K

logistical_data

product_code	packaging_unit	dimensions	weight	volume
4058075433243	Folding box 1	49 mm x 49 mm x 95 mm	43.00 g	0.23 dm ³
4058075616394	Shipping box 6	168 mm x 111 mm x 71 mm	348.00 g	1.32 dm ³

logistical_data_text

disclaimer_title

disclaimer_text